

Efficient, effective and flexible spill pans.

- No set up required
- Durable 3" foam logs allow spill pan to be driven into from any angle
- Heavy-duty 30 oz fabric is compatible for water, all hydrocarbons and most chemicals
- Simple to clean and store for repeated use
- Meets EPA regulations for spill containment
- All Spill Pans come equip with a patch kit
- Shortest lead-times in the industry
- Available in a variety of colors including Black, OD Green & Desert Tan
- Custom sizes are available upon request



SPECIFICATIONS

	US	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	8 oz/yd2	270 g/m2
Thickness	36 mils min	0.91 mm
Weight	30.0+ _ 2 oz/yd2	1020+ _ 70 g/m2
Tear Strength, Tongue D751B	120/120 lb min	534/534 N min
Breaking Yield Strength ASTM D 751, Grab Tensile, Proced.	625/600 lb min	2780/2670 N min
Low Temperature ASTM D 2136	Pass @ -40 F	Pass @ -40 C
Dimensional Stability ASTM D 1204, 212 F- 1 hr	2.5% max each direction	
Adhesion - Heat Sealed Seam ASTM D 751, Dielectric Weld	25 lb/2 in min	111 N/5 cm min
Bursting Strength ASTM D 751, Ball Tip	1000 lb min	4450 N
Hydrostatic Resistance ASTM D 751, Method A	800 psi min	540 N/sq cm min
Blocking Resistance ASTM D 751, 180 F/82 C	# 2 Rating max	
UV Resistance	8000 hrs	
Puncture Resistance ASTM D 4833	220 lb min	1110 N min

Gallons and Dimensions by Wall Size

Width	Length	3"/Gal	3"/Outside Dims
10'	10'	187	10' 6" x 10' 6"
10'	20'	374	10' 6" x 20' 6"
12'	36'	807	12' 6" x 36' 6"
14'	54'	1413	14' 6" x 54' 6"

Fabric: 30 oz. Hydrocarbon/chemical resistant
Standard colors: black, tan and green

Berg Company
16124 E Euclid Ave
Spokane, WA 99216
O: 509.624.8921
TF: 800.228.8277

CAGE 4JKJ9
DUNS 78-059-3856
www.bergco.com

