

Efficient, effective and flexible foam containment berms.

- Durable foam logs allow vehicles to drive over them and still retain their original shape
- Foam logs are covered with a fuel resistant polyethylene
- Easily drains through 3/4" drains
- Heavy-duty 30 oz fabric is compatible for water, all hydrocarbons and most chemicals
- Meets US regulations for spill containment
- Easy cleaning and storage allows for repeated use
- Includes a patch kit and 20 extra zip ties
- Available in a variety of colors including Black, OD Green, Desert Tan and Blue
- Custom sizes are available upon request



SPECIFICATIONS

	US	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	8 oz/yd ²	270 g/m ²
Thickness	36 mils min	0.91 mm
Weight	30.0+/- 2 oz/yd ²	1020+/- 70 g/m ²
Tear Strength, Tongue D751B	120/120 lb min	534/534 N min
Breaking Yield Strength ASTM D 751, Grab Tensile, Proced.	625/600 lb min	2780/2670 N min
Low Temperature ASTM D 2136	Pass @ -40 F	Pass @ -40 C
Dimensional Stability ASTM D 1204, 212 F- 1 hr	2.5% max each direction	
Adhesion - Heat Sealed Seam ASTM D 751, Dielectric Weld	25 lb/2 in min	111 N/5 cm min
Bursting Strength ASTM D 751, Ball Tip	1000 lb min	4450 N
Hydrostatic Resistance ASTM D 751, Method A	800 psi min	540 N/sq cm min
Blocking Resistance ASTM D 751, 180 F/82 C	# 2 Rating max	
UV Resistance	8000 hrs	
Puncture Resistance ASTM D 4833	220 lb min	1110 N min

Gallons and Dimensions by Wall Size

Width	Length	4"/Gallons	4"/Outside Dims
10'	10'	249	10' 8" x 10' 8"
10'	20'	499	10' 8" x 20' 8"
12'	36'	1077	12' x 36' 8"
14'	54'	1885	14' 8" x 54' 8"

Fabric: 30 oz. Hydrocarbon/chemical resistant

Standard colors: black, tan and green

Berg Company

16124 E Euclid Ave
Spokane, WA 99216
O: 509.624.8921
TF: 800.228.8277

CAGE 4JKJ9
DUNS 78-059-3856
www.bergco.com

