



Easy to set up and use.

- SnapUp support provides a sturdy side wall for excellent spill containment
- 100% usable interior space
- Heavy-duty 30 oz fabric is compatible for water, all hydrocarbons and most chemicals
- Meets EPA regulations for spill containment
- Grommets every 6" in skirt allows for repeated use
- Patch Kit comes standard with every SnapUp Berm
- Available in a variety of colors including Black, OD Green, Desert Tan and Blue
- Custom sizes are available upon request



SPECIFICATIONS

	US	Metric
Base Fabric Type	Polyester	
Base Fabric Weight (nominal)	8 oz/yd ²	270 g/m ²
Thickness	36 mils min	0.91 mm
Weight	30.0+ _ 2 oz/yd ²	1020+ _ 70 g/m ²
Tear Strength, Tongue D751B	120/120 lb min	534/534 N min
Breaking Yield Strength ASTM D 751, Grab Tensile, Proced.	625/600 lb min	2780/2670 N min
Low Temperature ASTM D 2136	Pass @ -40 F	Pass @ -40 C
Dimensional Stability ASTM D 1204, 212 F- 1 hr	2.5% max each direction	
Adhesion - Heat Sealed Seam ASTM D 751, Dielectric Weld	25 lb/2 in min	111 N/5 cm min
Bursting Strength ASTM D 751, Ball Tip	1000 lb min	4450 N
Hydrostatic Resistance ASTM D 751, Method A	800 psi min	540 N/sq cm min
Blocking Resistance ASTM D 751, 180 F/82 C	# 2 Rating max	
UV Resistance	8000 hrs	
Puncture Resistance ASTM D 4833	220 lb min	1110 N min

Fabric: 30 oz. Hydrocarbon/chemical resistant
Standard colors: black, tan and green

Width	Length	8"/Gal	8"/Outside Dims	12"/Gallons	12"/Outside Dims
10'	10'	479	11' 4" x 11' 4"	748	12' x 12'
10'	20'	997	11' 4" x 21' 4"	1496	12' x 22'
12'	36'	2154	13' 4" x 37' 4"	3232	14' x 38'
14'	54'	3770	15' 4" x 55' 4"	5655	16' x 56'

Berg Company

16124 E Euclid Ave
Spokane, WA 99216
O: 509.624.8921
TF: 800.228.8277

CAGE 4JKJ9
DUNS 78-059-3856

www.bergco.com

